

PROTECTA-LINE (25MM – 63MM DIAMETER)

MECHANICAL COMPRESSION FITTINGS

PRODUCT DATA SHEET




Mechanical Compression Fittings for use with Protecta-Line Pipe (25mm to 63mm). Full barrier performance without any requirement for additional wrapping.

RANGE / PRESSURE RATING

Product Range		Diameter size (mm)	Pressure rating
<ul style="list-style-type: none"> ■ Couplers ■ Reducers ■ Copper Transition Couplers ■ Equal Tees 	<ul style="list-style-type: none"> ■ 90° Elbows ■ MI Transition Fittings ■ FI Transition Fittings ■ 90° FI Transition Elbows. 	25 - 63mm diameter	12.5 bar

COLOUR

Materials	Colour
Acetal and nylon. Nitrile seals.	Black body with green pipe inserts 

STANDARDS / APPROVALS

BS 8588
(BSI Kitemark
Certificate KM 695717)

WRAS Approved
for use with
Protecta-Line
(1511343)

WEIGHTS

All weights are published in the GPS Protecta-Line Product and Technical Guide.

DIMENSIONS

All dimensions are published in the GPS Protecta-Line Product and Technical Guide.

IDENTIFICATION MARKING

- Nuts of the fittings are embossed with the text PHILMAC and PA
- Fittings are supplied individually bagged and labelled.
- Labelled with the following text:
 - GPS Protecta-Line
 - Installations Instructions
 - GPS contact details
 - GPS item code
 - Item Description and Size