

# PROTECTA-LINE (NOMINAL DIAMETERS 63MM – 355MM)

## FERRULE OFF-TAKES

### PRODUCT DATA SHEET



Gunmetal, DZR brass, stainless steel and acetal fittings for installing live service off-takes in sizes 25mm, 32mm and 63mm from Protecta-Line mains pipes.

#### RANGE / PRESSURE RATING

Diameter size (mm)	SDR	Pressure rating	Material
25mm off-take: 63 - 355mm mains	11	12.5 bar water	PE80
32mm off-take: 63 - 355mm mains			
63mm off-take: 90 - 355mm mains			

#### MATERIALS

##### Materials

The fittings are manufactured from gunmetal, DZR brass and 316 Stainless Steel.

Off-take connections are made from black acetal.

All seals are made from WRAS approved grades of EPDM.

#### STANDARDS / APPROVALS

**BS 8588**  
(BSI Kitemark  
Certificate KM 695717)

Polyethylene pressure pipe with an aluminium barrier layer and associated fittings for potable water supply in contaminated land – Size 25mm to 630mm

**BS EN 12201-3**

Plastic piping systems for water supply, and for drainage and sewerage under pressure – Polyethylene (PE) Fittings.

**WRAS Approved**

#### WEIGHTS

All weights are published in the GPS Protecta-Line Product and Technical Guide.

#### DIMENSIONS

All dimensions are published in the GPS Protecta-Line Product and Technical Guide.